

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/010422 A1

(51) International Patent Classification⁷: **F16L 21/06**

(21) International Application Number:
PCT/KR2004/001821

(22) International Filing Date: 22 July 2004 (22.07.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0052141 28 July 2003 (28.07.2003) KR
10-2004-0020596 26 March 2004 (26.03.2004) KR

(71) Applicant and

(72) Inventor: KIM, Su Gen [KR/KR]; Janwoo Officetel
No.320, 339-4 Huam-dong, Yongsan-gu, Seoul 140-901
(KR).

(74) Agent: SHIN, Dongjoon; No. 402, Seocho First Bldg,
1624-2 Seocho-dong, Seocho-gu, Seoul 137-878 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PIPE JOINT DEVICE BY FLANGE



(57) Abstract: A pipe joint device using flanges is disclosed. The pipe joint device includes: flanges mounted to ends of pipes to be coupled together or ends of both a pipe and a pipe joint to be coupled together, the flange having at least one ring groove around an outer circumferential surface thereof; a packing mounted to the flanges having inner rings around an inner circumferential surface thereof to closely engage with the ring grooves of the flanges; and a clamp having a packing seat to seat the packing therein, with a support sidewall formed by a radial inward extension of each side of the clamp, the clamp being divided into a plurality of clamp parts so that the clamp parts are placed around the packing and are fastened together by a locking member.